



15 Year Commercial Architectural Glass Warranty for Diamon-Fusion® Protective Coating

Commercial glass surfaces treated with the patented Diamon-Fusion coating are guaranteed to maintain contact angles of at least 70 degrees with sliding angles of no more than 30 degrees for 15 years, as long as manufacturer maintenance is followed and no harsh or abrasive cleaners are used. No Revitalizer™ is needed to satisfy this warranty for the first 15 years.

DOUBLE YOUR WARRANTY: After the initial 15-year term commencing with the Diamon-Fusion application, Diamon-Fusion International (DFI) will extend your warranty for three (3) additional five (5) year periods provided that you have DFI's Revitalizer™ product applied by an authorized applicator at the beginning of each five (5) year period.

DFI also warrants that Diamon-Fusion chemically bonds to glass creating a protective coating that, when applied by trained professionals, the coating is guaranteed not to haze, chip, crack, peel, or discolor for the lifetime of the glass.

In the event Diamon-Fusion low maintenance coating fails to comply with this warranty, DFI will provide materials necessary for retreatment. DFI's liability is limited to the cost of replacing chemical materials and will in no way extend to indirect, incidental or consequential damages incurred in relationship to this product.

THE FOREGOING WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES OF ANY KIND INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. COMPANY SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THIS PRODUCT. NOTE, SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MIGHT NOT APPLY TO YOU AS THE ORIGINAL PURCHASER. THIS LIMITED WARRANTY GIVES THE ORIGINAL PURCHASER SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE. COMPANY SHALL BE THE SOLE JUDGE AS TO WHETHER MANUFACTURER MAINTENANCE RECOMMENDATIONS HAVE BEEN FOLLOWED, AND IF IN COMPANY'S JUDGMENT THE PRODUCT FAILURE HAS ARISEN FROM IMPROPER CARE OR FAILURE TO FOLLOW COMPANY'S RECOMMENDATIONS, THEN COMPANY SHALL BE RELEASED FROM ANY OBLIGATION OR LIABILITY UNDER THIS LIMITED WARRANTY.

Diamon-Fusion Treated Commercial Architectural Glass Maintenance Instructions

Commercial glass treated with Diamon-Fusion should be cleaned with soapy water, a washer and a squeegee. Avoid cleaning glass in direct, hot sunlight. Please note, in extreme situations or where the environment has been manipulated (for example, where glass is exposed to sprinklers, pool cleaners, leaching, drainage issues, submerged areas and other forms of man-made water contact), a simple maintenance routine should be followed to keep deposits from developing on the coating over time.

Other cleaning products that can be safely used on Diamon-Fusion treated glass include ammonia free or pH neutral glass cleaner. Do not use harsh or abrasive cleaners on treated surfaces under any circumstances.

